

553, 447

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 October 2004 (28.10.2004)

PCT

(10) International Publication Number
WO 2004/092050 A1

(51) International Patent Classification⁷: **B81C 1/00**

(21) International Application Number:
PCT/SE2004/000561

(22) International Filing Date: 8 April 2004 (08.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0301144-2 17 April 2003 (17.04.2003) SE

(71) Applicant (for all designated States except US): **MICRO-MUSCLE AB** [SE/SE]; Westmansgatan 29, S-582 16 Linköping (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JAGER, Edwin**

[NL/SE]; Mjärdevigatan 9, S-584 22 Linköping (SE).
KROGH, Magnus [SE/SE]; Mårdtorpsgatan 31, S-584 32 Linköping (SE).

(74) Agent: **ALBIHNS GÖTEBORG AB**; Box 142, S-401 22 Göteborg (SE).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: METHOD FOR PRODUCING A MICROMACHINED LAYERED DEVICE

cont.



(57) Abstract: Method for producing a micromachined layered device comprising a membrane layer and a first layer on one side of the membrane layer and a second layer on the opposite side of the membrane layer, the method comprising the following steps: d) a membrane layer is applied on a substrate; e) a window in the substrate is opened so as to free the membrane layer in order to enable the adding of layers from both sides of the membrane layer while the substrate is made into a frame that supports the membrane layer during the processing; f) at least one layer is added on each side of the membrane either simultaneously or on one side at a time; d) the device is cut out and removed from the substrate frame.

WO 2004/092050 A1



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*